

License deactivation on Windows

This guide outlines how to deactivate a license of WebSpellChecker Server installed on a Windows server. After a successful license deactivation, you can reuse a license with a fresh installation on a new server.

1. Launch Deactivate License service. You can launch license deactivation service either directly from Windows graphic user interface (GUI) or using command line interface (Command Prompt). Both ways are described in this section.

Option A: Windows GUI

Go to Windows Start → All Programs → WebSpellChecker → AppServer → Deactivate License

Option B: Command Prompt

Open Command Prompt → Switch to [WebSpellChecker_Installation_Path]/AppServer → Run AppServerX.exe -deactivateLicense

Alternatively, you can execute **AppServerX.exe** with **-deactivateLicense** and **-y** parameters as follows for a silent automatic license deactivation:

```
AppServerX.exe -deactivateLicense -y
```

2. Select the license deactivation mode. You can choose between **automatic** or **manual** license deactivation mode.

Option A: Automatic License Deactivation

2.1. If you prefer to deactivate license automatically, and Internet connection is available on your machine, press **Enter**. The automatic license deactivation is provided by default.

```
.../AppServerX.exe -deactivateLicense
```

```
Do you want the installer to attempt to deactivate your license automatically?
The automatic deactivation requires the Internet connection available on this machine.
Otherwise, please proceed with the manual deactivation instead.
Enter 'y' or 'n' [y]: y
```

```
Congratulations! Your License Ticket ID '*****' has been deactivated successfully. Now you can reuse
this license with a fresh installation.
```

If no valid license is found, you will get the following error:



Error. Failed to deactivate the license. No valid license is found on this machine.

Option B: Manual License Deactivation

2.1. If your machine doesn't have Internet connection configured, select manual license deactivation mode by typing **'n'**.

```
.../AppServerX.exe -deactivateLicense
```

```
Do you want the installer to attempt to deactivate your license automatically? The automatic deactivation
requires the Internet connection available on this machine. Otherwise, please proceed with the manual
deactivation instead.
Enter 'y' or 'n' [y]: n
```

Deactivate License by copying and pasting the next Deactivation link into the browser window:

```
https://webspellchecker.com/api/licensing/v1/process-license?data=3:SCv4n4AFLiB6pQXSYv9
/zTRxxLIwhzjjKiAUx2KKvv8jzmmw90s3KI964fe0DuT/Xwm4EtqTsc/m68bRtdw/GfZxuA0X3eVH5Som613HN1Q0RFxZd1JJ2h0L0hhZ2Rv%
2B1WxLSQsUvW0QRJsF5u1DVZH9R=
```

2.2. Once the manual license deactivation mode is selected, a **Deactivation link** will be generated based on your current License Ticker ID and unique machine hardware characteristics.

Use this Deactivation link to deactivate license. Copy the entire Deactivation link and past into the browser window on the machine with the Internet connection. If the used Deactivation link is valid, the license will be deactivated successfully. The following message will be shown in the browser window:



Congratulations! Your License Ticket ID '*****' has been deactivated successfully. Now you can reuse this license with a fresh installation.

If no valid license is found, you will get the following error:



Error. Failed to deactivate the license. No valid license is found on this machine.