

Configuring SCAYT plugin for CKEditor 4

This guide outlines the main steps that you need to follow in order to integrate and configure the SCAYT plugin for [CKEditor 4](#). All the described steps are provided for the Server version of SCAYT.

1. Initialize CKEditor 4

Before integrating and configuring the SCAYT plugin, CKEditor 4 should be properly configured in your web application. If you haven't done it yet, please download the latest version of the CKEditor 4 standard package and refer to [CKEditor Quick Start Guide](#).

2. Activate SCAYT plugin

If you are using the standard package of CKEditor 4, the SCAYT plugin is already there, which is pointed to the free services. To accomplish migration to the trial or paid version of SCAYT Server, the additional SCAYT parameters must be added to the CKEditor **config.js** file.

2.1. Specify path to the SCAYT plugin (wscbundle.js or ckscayt.js if you have older versions) using **scayt_srcUrl** parameter.

```
config.scayt_srcUrl = "http(s)://your_host_name/virtual_directory/wscbundle/wscbundle.js";
```

2.2. Specify the path to the service installation where spelling and grammar check requests will be processed:

```
config.scayt_serviceProtocol='http(s)';  
config.scayt_serviceHost='your_host_name';  
config.scayt_servicePort = '443';  
config.scayt_servicePath = 'virtual_directory/api'; // by default the virtual_directory is wscservice
```



If you are using the old deployment where the entry point is the SSRV.CGI component, please refer to the sample below.

```
config.scayt_serviceProtocol='http(s)';  
config.scayt_serviceHost='your_host_name';  
config.scayt_servicePort = '443';  
config.scayt_servicePath = 'virtual_directory/script/ssrv.cgi';
```

3. Adjust default settings

Define additional SCAYT parameters, for example, start SCAYT spelling and grammar automatically, change default language, and others. For details, refer to [SCAYT Parameters for CKEditor 4](#) guide.

```
config.scayt_autoStartup = true; // enable spell check as you type on the editor load  
config.scayt_autoStartup = true; // enable grammar check  
config.scayt_sLang = 'auto'; // sets the default language
```



Check a demo page with [SCAYT plugin for CKEditor](#) on our website.

Still have a question?

Please feel free to contact our [technical team](#) if you are having any difficulties with the configuration.

Can be also useful:

- [SCAYT Parameters for CKEditor 4](#)
- [Configuring WSC Dialog plugin for CKEditor 4](#)
- [Initializing WProofreader in CKEditor 4](#)